



Low profile goggle

KEY FEATURES

- Excellent protection against liquid splash and dust
- Wide panoramic vision
- Universal nose bridge
- Soft TPR frame
- Indirect ventilation
- Adjustable head strap
- Optical class 1 polycarbonate lens
- Can be worn over spectacles



CLEAR

ORDERING INFORMATION

VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	 BM30CLRAF	2C-12 ▶ 1BT 9 	▶ EN 166 3 4 9 BT  BM30	Impacts, UV radiations, dust, chemicals and molten metals	Anti-scratch+anti-fog



GENERAL SPECIFICATIONS

LENS BASE	6mm
WEIGHT	119g

PACKAGING

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	100

COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS	Polycarbonate	Robust
BODY	PVC	Flexible
HEADBAND	Textile Elastic	Adjustable and elastic
HEADBAND CLIP	Polycarbonate	For length adjustment

LENS MARKINGS

LENS FILTER TYPE:
2C UV

SCALE NUMBER (SHADE):
1.2 Clear

► Identity of the manufacturer

OPTICAL CLASS:
1 High optical quality

MECHANICAL STRENGTH:
B Medium energy impact, resists a 6mm, 0.86 g ball at 120m/s
T Protection against high-speed particles at extreme temperatures

PERFORMANCE:
9 Molten metal splash

CE Certification mark

FRAME MARKINGS

► Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

MECHANICAL STRENGTH:
3 Liquid droplets or splashes
4 Large dust particles > 5 µm
9 Molten metal and hot solids

B Medium energy impact, resists a 6mm, 0.86 g ball at 120m/s
T Protection against high-speed particles at extreme temperatures

CE Certification mark

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.