# **BM20**

Classic Adjustable Sports Style Safety Spectacle

## FEATURES

- > Sports style
- > Soft, adjustable, anti-slip nose bridge
- Multi-functional for a personalised fit: length adjustable temples and lens inclination adjustment
- Co-injected bi-colour temples with flexible TPE ends enhance overall fit and comfort
- > Anti-Scratch & Anti-fog





## CERTIFICATION

ITEM NO.	VERSIONS		LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
BME00020KA	CLEAR	$\bigcirc$	2C-1.2 <b>&gt;</b> 1FT <b>( (</b>	▶ EN 166 FT C € 분%/ Z87+	Impacts, UV radiations	
BME00020KO	INDOOR/ OUTDOOR		5-1.7 <b>₽</b> 1F <b>C</b> €	▶ EN 166 FT C € \ 287+	Impacts, UV and Sun glare	Anti-scratch + Anti-fog / UV400 / Moisture repellent



#### GENERAL SPECIFICATIONS

LENS BASE	9.25mm		
WEIGHT	23g		
PACKAGING			
Individually contained in a polythene b	bag with a Euroslot		
Individually contained in a polythene b	bag with a Euroslot		

## **COMPONENT SPECIFICATION**

	LENS Polycarbonate One piece moulded lens with side protection	COMPONENT	MATERIAL	FEATURES
Polycarbonate		LENS	Polycarbonate	

# LENS MARKINGS

#### LENS FILTER TYPE:

- 2C UV
- 5 Solar

#### SCALE NUMBER (SHADE):

- 1.2 Clear
- 1.7 Indoor Outdoor
- Identity of the manufacturer

#### **OPTICAL CLASS:**

1 High optical quality

#### **MECHANICAL STRENGTH:**

- **F** Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures
- C€ Certification mark

# FRAME MARKINGS

Identity of the manufacturer

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

#### **MECHANICAL STRENGTH:**

- F Low energy impact, resists a 6mm, 0.86g ball at 45m/s
- T Protection against high-speed particles at extreme temperatures

#### C€ ₭ Certification mark

### **CLEANING AND STORAGE**

CLEANING:	The lenses should be cleaned regularly.
MAINTENANCE:	Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.
STORAGE:	All products must be stored in a dry and clean environment.

#### **EUROPE**

#### www.globusgroup.com

- E: sales@globusgroup.com
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

## MIDDLE EAST AND AFRICA www.globusgroup.com/gcc

- E: gcc@globusgroup.com T: +971 4 882 9962
- **F:** +971 4 882 9963

Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



© 2019 Globus (Shetland) Ltd | BMK-DATA-BM20-0223\_1

EC-Type certification issued by: 0194: INSPEC, 56 Leslie Hough Way, Salford, Greater Manchester, M6 6AJ, United Kingdom

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.