Middle East / India



## PRODUCT NUMBER: 2058685 CRYOGENIC

Protection against small drops of liquid gas up to -  $170^{\circ}\mathrm{C}.$ 

### Overview

Reference Number 2058685

Product Type Gloves

Range Specific Protection

Brand Honeywell

Brand formerly known as SPERIAN

#### Industry

Chemical Industries
Petro-chemical

#### **Product Use**

Protection against small drops of liquid gas up to - 170°C.

## **Features & Benefits**

#### Feature

Water-repellent silicone cowhide grain leather glove Fully lined with 2 aluminium/fleece layers Gunn cut, winged thumb, crispin type Reinforcement between thumb and index 200 mm split leather cuff Velcro® adjustment strap on side of the palm

#### Benefit

COMFORT

The US assembly, the winged thumb and flexibility of the materials used make this glove anatomical, thus providing excellent comfort.

The Velcro fastening tab gives the glove good support.

#### RESISTANCE

### CRYOGENIC - 2058685

The silicone cowhide grain leather ensures good flexibility, even at a low temperature as well as water repellence and good mechanical protection.

Its polar double insulation offers outstanding protection against the cold and rays.

The reinforcement between the thumb and index finger increases the glove's mechanical resistance and durability by strengthening the areas of wear.

HYGIENE

The hide cuff offers good forearm protection against mechanical hazards and limits any risk of intrusion.

### **Technical Description**

#### Description

CE CATEGORY : II Intermediary risks In accordance with standards : EN 420-2003 EEC Basic standards EN 388-2003 Mechanical Hazards EN 511-2006 Cold protection

CHARACTERISTICS : Water-repellent silicone cowhide grain leather glove Fully lined with 2 aluminium/fleece layers Gunn cut, winged thumb, crispin type Reinforcement between thumb and index 20 cm split leather cuff Velcro® adjustment strap on side of the palm

# Product Technology

Cut and Sewn

Coating Type Leather

Thickness 1.1/1.3 mm

Harmlessness

In conformity with the European standards

Dexterity

Class 5

**Sizes** 9 to 11

# EN 388 - Mechanical Hazards Abrasion Resistance

Abrasion resistance	3
Cutting resistance	2
Tear resistance	2
Puncture resistance	2

# EN 511- Protection in cold temperatures:

Resistance to conductive cold	2
Resistance to contact cold	2
Water permeability	0

# Packaging Label

Tagging CE HONEYWELL 2058685 XX EN 420 EN 388 : 3222 EN 511 : 220

### Certifications

EC Category PPE 2 EC Certificate Number 0075/797/162/01/09/0001

**EC** Attestation

**EC Attestation Number** 0075/797/162/01/09/0001

## **Additional Information**

User Manual UI 105

**User Information Sheet** 105

## Maintenance

**Storage Information** Minimum packaging 1 pair. Cartons of 25 pairs.

#### **Care Instructions**

In order to keep its properties, this article should not be cleaned.

C Honeywell International Inc.