

HyFlex® 11-630 11-638



CUT PROTECTION



M MEDIUM

MECHANICAL PROTECTION

STYLE #	CONSTRUCTION	LINER MATERIAL	COATING MATERIAL	CUFF STYLE	COLOUR	LENGTH MM	EN SIZE	PACKAGING
11-630 	Palm coated	NylonLycra® Kevlar® HPPECotton	Polyurethane	Elasticated cuff	Grey coating on grey liner	215 - 275	6, 7, 8, 9, 10, 11	12 pairs in a bag, 12 bags in a carton
11-638	Palm coated	NylonLycra® Kevlar® HPPECotton	Polyurethane	Elasticated long cuff	Grey coating on grey liner	290 - 340	6, 7, 8, 9, 10, 11	12 pairs in a bag, 12 bags in a carton



Dexterity with superb cut resistance for optimal productivity

PRIMARY INDUSTRIES



IDEAL APPLICATIONS

- Glass manufacturing
- Aeronautics
- Assembly of white goods
- Plastics injection and moulding
- Assembling metal parts and components
- Handling sharp or irregular-edged metal parts



DESCRIPTION

- The liners of the HyFlex® 11-630 and 11-638 gloves have a yarn structure that contains an optimal rate of HPPE. This offers high levels of cut resistance, for a safe use in controlling, handling and assembly applications involving contacts with sharp pieces.
- The Lycra® in the liners of both gloves, as well as the polyurethane coating, provides excellent flexibility and fit.
- The specific formulation of the polyurethane dipping provides a secure grip on dry or slightly oily pieces.
- The PU formulation also increases abrasion resistance on the gloves' work surface.



CATEGORY II

Ansell Healthcare Europe N.V.

Riverside Business Park Block J Boulevard International 55 B-1070 Brussels, Belgium
Tel. +32 (0) 2 528 74 00 Fax +32 (0) 2 528 74 01 Fax Customer Service +32 (0) 2 528 74 03
<http://www.ansell.eu> E-mail info@ansell.eu

Ansell