

# HyFlex® 11-927


MECHANICAL PROTECTION



OIL-REPELLENT



MEDIUM

STYLE #	CONSTRUCTION	GAUGE	LINER MATERIAL	COATING MATERIAL	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-927 	Knitted	13	Nylon HPPE	Nitrile	¾ Dipped	Knitwrist	Light grey, dark grey and black	6, 7, 8, 9, 10, 11	215-242	12 pairs in a bag, 12 bags in a carton



## DESCRIPTION

- The first HyFlex® glove to combine advanced cut resistance, oil repellence and oil grip in a single flexible glove. Ideal for handling sharp metal components coated in oil or lubricant.
- Patented Ansell Grip™ technology uses microscopic channels to wick away oil & moisture from part surfaces and tools, providing industry-leading wet and oil grip for added safety and efficiency.
- The design combines a ¾ nitrile dip with grip. This ensures EN Level 4 abrasion protection and long-lasting EN Level 3 cut resistance.
- The ¾ dip geometry means extra protection against oil exposure and knuckle abrasion.
- A new former shape offers superior fit. Together with a highly flexible polymer and a wide range of sizes, this enables more agility in medium-duty applications.
- Greys and blacks mask dirt in oily, grimy and gritty environments.

## REMARKS

- Fit for special purpose

## FEATURED TECHNOLOGY

Ripel™



Intercept®



Ansell Grip



## Ultimate performance for oily environments

### PRIMARY INDUSTRIES



### IDEAL APPLICATIONS

- Handling & assembly of sharp components with oil/grease coating
- Handling of machined parts coated with light oil
- Assembly of engine & transmission drive trains
- Light metal presses
- Machining, metalworking
- Maintenance
- Body shops
- Primary assembly



EN 388:2016 EN 388:2003  
4342B 4342

**CATEGORY II**

Print date: 26-11-2016

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

http://www.ansell.eu • E-mail info@ansell.eu

