HyFlex® 11-518



Mechanical Protection

Cut Protection

Light



Ultralight duty cut resistant glove

DESCRIPTION

- The first 18-gauge glove with EN Level 3 cut protection, and EN Level • 3 abrasion protection for extended glove life.
- Dyneema® Diamond Technology fibre and a thin PU coating bring a new degree of dexterity and tactility for applications with cut risks.
- An ultralight fabric and tailored fit, including D3 Pinky Knitting, create a sensation of barehand contact.
- The soft ultralight-duty seamless liner breathes to keep hands cool and dry, and offers enhanced flexibility and fingertip sensitivity with superior comfort
- Comprehensive 6-11 sizing ensures optimum fit and comfort for every worker.
- In field trials the HyFlex® 11-518 was preferred by nearly 70% of workers over thicker gloves, a preference that correlates with compliance.

PRODUCT DETAILS

| Construction | Knitted |
|------------------|-------------------------------------------------|
| Liner material | Dyneema® Diamond Technology Nylon Spandex |
| Gauge | 18 |
| Coating material | Polyurethane |
| Finishing | Palm coated |
| Cuff style | Knitwrist |
| Colour | Blue |
| EN Sizes | 6,7,8,9,10,11 |
| Length (mm) | 210-265 |
| Packaging | 12 pairs in a bag; 12 bags in a carton |

Print date 13-02-2020

Ansell Healthcare Europe N.V. (European Head Office) Riverside Business Park, Block J Boulevard International 55, 1070 Brussels, Belgium Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03 http://www.ansell.eu • E-mail info@ansell.eu



IDEAL APPLICATIONS

- Final assembly
- Handling & assembly of small or ultra-fine sharp parts
- Injection molding parts assembly
- Machining -special metal blends
- Packaging areas with risk of cut
- Stamping light & dry Wire assembly & fastening

PRIMARY INDUSTRIES



STANDARDS AND CERTIFICATIONS



CATEGORY II

FEATURED TECHNOLOGY



EXTRA FEATURES



