

**MANAGER S3**

*Product Reference*    Manager  
*ENISO20345:2011*    S3 SRC ESD  
*Sizes*                    38-46  
*Weight (s. 41)*        540 gr.

**Model description:** Leather shoe, water repellent, black, cambrella lining, antistatic, puncture resistant SJ Flex sole, shock proof, antislip, composite toe cap, S3 ESD, PU sole + rubber part.

**Application areas:** Construction, Manufacturing.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



		Description	Measure Unit	Result	EN345 required	
Complete shoe	Protection of toes: composite tip resistant to: A shock of 200 J Pressure of 1500 kg Sole: SJ Flex resistant to 1100N	Impact resistance (Clearance after shock)	Mm	15	>14	
		Compressive strength (after clearance compression)	Mm	17,5	14	
	Anti-shock system: Low-Density polyurethane and profile of the heel	Shock absorption in heel	J	>41	>20	
Upper	Leather, water repellent, black	Permeability to water vapor	Mg/m2 hour	>2,0	>0,8	
		Thickness 1,6mm	Permeability coefficient	Mg/cm2	>25,6	>20
			Water repellent	Minute	>90	<60
Front	Thickness 1,2mm	Permeability coefficient	Mg/cm2	>34,3	>30	
Lining	Cambrealla black	Permeability to water vapor	Mg/cm2 hour	>2,1	>2	
Back	Thickness 1,0mm	Permeability coefficient	Mg/cm2	>45	>30	
Insole	Antistatic, absorbent, resistant to abrasion and to exfoliation	Abrasion resistance	Cycles	>400	>400	
Outsole	Antistatic double density polyurethane injected directly onto the upper	Abrasion resistance (volume loss)	Mm3	110	<150	
		Shock absorption, anti-slip, abrasion resistant, mineral oils and weak acids	Oil resistance (volumen variation AV)	%	+1,0	<+12
			Coefficient of adhesion of the outsole	-	0,18	>0,15

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*