

Medium attenuation, slim design

3M™ Peltor™ X2 Ear Defenders



SNR 31dB

- Slim-line cups for moderate to high attenuation (SNR 31dB) that meets the needs of most industrial applications.
- Lightweight design.
- Simple colour coding: yellow, indicating moderate to high attenuation.



3M™ Peltor™ X2A Ear Defenders - Standard headband

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	19.0	14.1	22.2	31.1	39.7	36.6	37.0	37.9
Standard Deviation (dB)	4.5	2.2	2.1	2.7	3.2	3.2	3.7	3.4
Assumed Protection (dB)	14.5	11.9	20.1	28.4	36.6	33.5	33.3	34.5

SNR = 31dB H = 34dB M = 29dB L = 20dB



3M™ Peltor™ X2P3 Ear Defenders - Helmet mounted version

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	15.9	13.8	20.2	30.0	37.7	35.4	34.9	35.8
Standard Deviation (dB)	4.6	2.8	2.1	3.2	2.6	3.0	3.0	4.7
Assumed Protection (dB)	11.3	11.0	18.1	26.8	35.1	32.4	31.9	31.1

SNR = 30dB H = 33dB M = 28dB L = 19dB